

WARREN

WFT-2010 Series

AccuMaxx Pull Type Lime & Fertilizer Spreaders

Maximize your spread pattern with a Warren AccuMaxx spreader. Uniquely shaped spinner discs and deflectors work together to provide an accurate and controlled even spread. Uniform fertilizer placement up to 90' and lime up to 75'.



The Warren WFT AccuMaxx line comes standard with a 3 speed ground wheel drive gearbox and hydraulic spinners. 6-Ton AccuMaxx pictured above.



www.spreaders.com
www.dumptrucks.com

Warren, Inc.
707 North Fir (P.O. Box 1719)
Collins, MS 39428

Phone: 601-765-8221
Fax: 601-765-4554
Toll Free: 800-228-4842

WFT-2010 Series Specifications



6 Ton AccuMaxx with Optional Stainless Steel Mesh Chain

Construction:

- 12 Gauge Stainless Steel Construction
- Welded in bed type jigs and fixtures for accurate fit & alignment
- Standard Duty Chassis: 5" x 2" Tubing

3 Ton:

- Single 6 ton axle design with 16.5L x 16.1 flotation tires
- 96" length x 72 3/4" wide x 36" tall
- Ground to Side Height: 74 1/2"
- Ground to Peak Height: 79"
- 97.5 Cubic Feet

6 Ton:

- Single axle design with 19L x 16.1 flotation tires
- 120" length x 84" wide x 45" tall
- Ground to Side Height: 84 1/2"
- Ground to Peak Height: 90"
- 180 Cubic Feet

Conveyor:

- Width: 20"
- #3 Pintle (Bar Every Link)
- Conveyor trough lined with UHMW
- Ground wheel driven by 3 speed gear box

Spinner Assembly

- 22.5" dished stainless steel spinners
- Dual hydraulic spinner motors
- Spinner speed controlled by hydraulic valve
- Tractor requires a hydraulic pump with 15GPM minimum @ 2,200 PSI

Options:

- Full Hydraulic Controls
- High Crop Model
- Various Tire Options Available
- Raven or TeeJet Controllers
- Tarps
- Lights
- Stainless Steel Mesh Chain



Distributed by:



www.spreaders.com
www.dumptrucks.com

Warren, Inc.
707 North Fir (P.O. Box 1719)
Collins, MS 39428

Phone: 601-765-8221
Fax: 601-765-4554
Toll Free: 800-228-4842